


## LED DISC 2



Please see the attached pages for detailed specifications.



|                                      |  |
|--------------------------------------|--|
| <b>Mounting:</b>                     | Recessed   |
| <b>Body material:</b>                | Steel & Aluminium  |
| <b>Colour:</b>                       | White RAL9016  |
| <b>LED module:</b>                   | First brand LED module   |
| <b>Colour temperature:</b>           | 2700k/3000k/4000k  |
| <b>Colour Rendering Index (CRI):</b> | CRI 80>  |
| <b>Driver:</b>                       | First brand driver   |
| <b>Emergency unit:</b>               | No   |
| <b>Movement sensor:</b>              | Available on request   |
| <b>Daylight control sensor:</b>      | Available on request   |
| <b>Operating temperature range:</b>  | 0°C to +40°C   |
| <b>IP Class:</b>                     | IP20   |
| <b>Power:</b>                        | 220-240V 50/60Hz   |
| <b>Lighting direction:</b>           | Direct   |
| <b>Reflector type:</b>               | White  |
| <b>Light distribution:</b>           | Symmetric  |
| <b>Diffuser:</b>                     | N/A  |
| <b>General data:</b>                 | 5 Years standard warranty,<br>possible extension with project<br>registration<br>Different lumen output or<br>wattage available on request<br>All other technical features<br>such as : Luminaire Eicacy,<br>LOR, Lumen maintenance L/B<br>etc. available in our pricelist<br>Wattage of products may vary<br>due to constant LED eicacy<br>improvements. Luminous lux<br>& Luminaire Power tolerance<br>+/- 10%.<br>System power consumption<br>(LED module & driver) depends<br>on components used |