

ACOUSTIC MENSA LUMINAIRE



ACOUSTIC MENSA LUMINAIRE

The acoustic panels are designed to absorb the echo and reverberation associated with open concept spaces, exposed concrete, exposed ceilings and large windows. For sound comfort, BAMBOO is available with an 8 mm thick acoustic panel as standard. Modern and decorative design for professional lighting


MARLITE UK

| Mounting: | Surface/Pendant |
|-------------------------------|-------------------------------|
| Body material: | PET |
| Colour: | Various RAL colours available |
| LED module: | First brand LED module |
| Colour temperature: | 2700K – 6500K |
| Colour Rendering Index (CRI): | CRI 80> Optional CRI 80> |
| Driver: | First brand driver |
| Emergency unit: | Available on request |
| Movement sensor: | Available on request |
| Daylight control sensor: | Available on request |
| Operating temperature range: | -20°c to +50°c |
| IP Class: | IP20 |
| Power: | 220-240V 50/60Hz |
| Lighting direction: | Direct |
| Reflector type: | N/A |
| Light distribution: | Symmetric |
| Diffuser: | Opal diffusor |

ACOUSTIC MENSA LUMINAIRE



Images



Marlite UK reserves rights to introduce any construction or technical changes in the products.