

WALL SPEC ND


Wall mounted adjustable LED luminaire

Mounting:	Wall mounted
Body material:	Steel and aluminium
Colour:	Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
LED module:	Osram LED modules included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI):	>80
Driver:	Electronic driver , Dali on request
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting with possibility of light direction adjustment
Reflector type:	Integrated lens
Light distribution:	Symmetric
Reflector beam angle:	24° / 40°
General data:	5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5840.7200/830/24D	7200	92	3000	Ra > 80	35.000	5	4	9,60
5840.7200/840/24D	7200	92	4000	Ra > 80	35.000	5	4	9,60
5840.7200/830/40D	7200	92	3000	Ra > 80	35.000	5	4	9,60
5840.7200/840/40D	7200	92	4000	Ra > 80	35.000	5	4	9,60
5840.9600/827/24D	9600	96	2700	Ra > 80	50.000	5	4	9,60
5840.9600/830/24D	9600	96	3000	Ra > 80	50.000	5	4	9,60
5840.9600/840/24D	9600	96	4000	Ra > 80	50.000	5	4	9,60
5840.9600/827/40D	9600	96	2700	Ra > 80	50.000	5	4	9,60
5840.9600/830/40D	9600	96	3000	Ra > 80	50.000	5	4	9,60
5840.9600/840/40D	9600	96	4000	Ra > 80	50.000	5	4	9,60
5840.14400/827/24D	14400	140	2700	Ra > 80	50.000	5	4	9,60
5840.14400/830/24D	14400	140	3000	Ra > 80	50.000	5	4	9,60
5840.14400/840/24D	14400	140	4000	Ra > 80	50.000	5	4	9,60
5840.14400/827/40D	14400	140	2700	Ra > 80	50.000	5	4	9,60
5840.14400/830/40D	14400	140	3000	Ra > 80	50.000	5	4	9,60
5840.14400/840/40D	14400	140	4000	Ra > 80	50.000	5	4	9,60

