

**BS LED**



Wall mounted, adjustable LED luminaire

- Mounting:** Wall mounted
- Body material:** Steel and aluminium
- Colour:** Standard White 9010, other RAL colours on request ( please add RAL code after index number )
- LED module:** Philips / Osram or Tridonic LED module included
- Colour temperature:** 2700K , 3000K or 4000K available
- Colour Rendering Index (CRI):** >80 in standard, other on request
- Driver:** Electronic driver
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20 in standard
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting with possibility of light direction adjustment
- Reflector type:** Integrated lens
- Light distribution:** Symmetric
- General data:** 5 Years standard warranty  
Different lumen output or wattage available on request  
All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6018.140/830	140	2	3000	Ra > 80	30.000	3	3	0,40
6018.140/840	140	2	4000	Ra > 80	30.000	3	3	0,40

