

## **MIRROR H**





Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5839.3600/830	3600	40	3000	Ra > 80	30.000	3	3	15,00
5839.3600/830/HM	3600	80	3000	Ra > 80	30.000	3	3	15.00

Wall mounted LED mirror

Wall mounted Mounting:

Body material: Steel, aluminium and glass

Standard Gray RAL 9006, other

RAL colours on request ( please add RAL code after index

number)

>80

LED module: LED modules included

Colour temperature: 3000K

Colour Rendering Index (CRI):

Colour:

Driver: Electronic driver included

N/A Emergency unit: Movement sensor: N/A Daylight control sensor: N/A

Operating temperature

0°C ... +40°C

IP Class: IP44

220-240V 50/60Hz

Lighting direction: Direct Reflector type: N/A Light distribution: Symmetric

General data: 3 Years standard warranty

> Available version with heating mat behind the mirror to prevent fog - HM in index number

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



