


PLAFO 1150 LED PND



Please see the attached pages for detailed specifications.



Direct/indirect version

| | |
|--------------------------------------|--|
| Mounting: | Pendant |
| Body material: | Steel & Aluminium |
| Colour: | Grey RAL9006 |
| LED module: | Tridonic or equivalent LED module included. |
| Colour temperature: | 3000k/4000k |
| Colour Rendering Index (CRI): | CRI 80> |
| Driver: | First brand driver |
| Emergency unit: | Yes |
| Movement sensor: | Available on request |
| Daylight control sensor: | Available on request |
| Operating temperature range: | 0°C to +40°C |
| IP Class: | IP20 |
| Power: | 220-240V 50/60Hz |
| Lighting direction: | Direct/Indirect |
| Reflector type: | Aluminium White |
| Light distribution: | Symmetric |
| Diffuser: | White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request. |
| General data: | 5 Years standard warranty, possible extension with project registration Different lumen output or wattage available on request All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist Wattage of products may vary due to constant LED efficacy improvements. Luminous lux & Luminaire Power tolerance +/- 10%. System power consumption (LED module & driver) depends on components used |