


One-LED Solo Emergency LED Lamp & Driver



Surface mounted box



Open area lens



Corridor lens



Non-maintained LED lamp and driver kit

- Mounting:** Ceiling mounted
- Body material:** Aluminium & polycarbonate
- Colour:** XXXXXX
- LED module:** Self contained LED emergency luminaire
- Colour temperature:** 6500K
- Colour Rendering Index (CRI)** >80 in standard
- Driver:** Omni-LED emergency LED driver
- Emergency unit:** 3hr non-maintained
- Movement sensor:** On request
- Daylight control sensor:** On request
- Operating temperature range:** -20°C ... +45°C
- IP Class:** IP20
- Power:** 220-240V 50/60Hz
- Reflector type:** N/A
- Light distribution:** Symmetric
- Diffuser:** N/A
- General data:** 5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our price list

Wattage of products may vary due to constant LED efficacy improvements. Luminous lux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used.

Index no.	Lumen output (lm)	Power (W)	Colour temp (K)	CRI	Lifetime (H)	Warranty (Years)	MacAdam (SDCM)	Weight (kg)
OL-SOLO	123/155	3.5	6500	>80	50,000	5	XXXX	XX