

LIGHTING SOLUTIONS

Track Spot Polaris



Please see the attached pages for detailed specifications.

| Mounting: | Track |
|-------------------------------|--|
| Body material: | Aluminium |
| Colour: | Black |
| LED module: | Osram - Power LED |
| Colour temperature: | 3000k/4000k |
| Colour Rendering Index (CRI): | CRI 90> |
| Driver: | First brand driver |
| Emergency unit: | No |
| Movement sensor: | Available on request |
| Daylight control sensor: | N/A |
| Operating temperature range: | 0°c to +40°c |
| IP Class: | IP20 |
| Power: | N/A |
| Lighting direction: | Direct |
| Reflector type: | Polycarbonate |
| Light distribution: | Symmetric |
| Diffuser: | N/A |
| General data: | 5 Years standard warranty, possible extension with project registration Different lumen output or wattage available on request All other technical features such as : Luminaire Eicacy, LOR, Lumen maintenance L/B etc. available in our pricelist Wattage of products may vary due to constant LED eicacy improvements. Luminous lux & Luminaire Power tolerance +/c 10% |

+/- 10%. System power consumption (LED module & driver) depends on components used



25 Romer Street, Bolton BL2 6BG Tel: 01204 867727 www.marliteuk.co.uk

