


**MAG 66**



Please see the attached pages for detailed specifications.



<b>Mounting:</b>	Modular ceiling n type in standard, mounting brackets for gypsum ceiling on request
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard White RAL9016, other RAL colours available on request
<b>LED module:</b>	Philips/Osram or Tridonic
<b>Colour temperature:</b>	3000k or 4000k
<b>Colour Rendering Index (CRI):</b>	>80 in standard, >90 on request
<b>Driver:</b>	Electronic driver in standard, DALI on request
<b>Emergency unit:</b>	On request
<b>Movement sensor:</b>	On request
<b>Daylight control sensor:</b>	On request
<b>Operating temperature range:</b>	0°c to +40°c
<b>IP Class:</b>	IP20
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct/Indirect
<b>Reflector type:</b>	White painted
<b>Light distribution:</b>	Symmetric
<b>Diffuser:</b>	Microprismatic (MPR) as standard
<b>General data:</b>	5 Years standard warranty, possible extension with project registration Different lumen output or wattage available on request All other technical features such as : Luminaire Eicacy, LOR, Lumen maintenance L/B etc. available in our pricelist Wattage of products may vary due to constant LED eicacy improvements. Luminous lux & Luminaire Power tolerance +/- 10%. System power consumption (LED module & driver) depends on components used