


## INDI BATTEN END MOUNT



Please see the attached pages for detailed specifications.



<b>Mounting:</b>	Surface or suspended
<b>Body material:</b>	Rigid power coated steel housing
<b>Colour:</b>	Standard White RAL9016. Other RAL colours on request
<b>LED module:</b>	Tridonic advanced module
<b>Colour temperature:</b>	4000k
<b>Colour Rendering Index (CRI):</b>	CRI 80>
<b>Driver:</b>	Tridonic
<b>Emergency unit:</b>	On request – Standard or DALI 3 hour emergency unit
<b>Movement sensor:</b>	On request
<b>Daylight control sensor:</b>	On request
<b>Operating temperature range:</b>	-20°c to + 45°c
<b>IP Class:</b>	IP20
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct
<b>Reflector type:</b>	N/A
<b>Light distribution:</b>	Symmetric
<b>Diffuser:</b>	60/90 optical lens control or D-shaped polycarbonate cover
<b>General data:</b>	<p>5 Years standard warranty, possible extension with project registration</p> <p>Different lumen output or wattage available on request</p> <p>All other technical features such as : Luminaire Eicacy, LOR, Lumen maintenance L/B etc. available in our pricelist</p> <p>Wattage of products may vary due to constant LED eicacy improvements. Luminous lux &amp; Luminaire Power tolerance +/- 10%.</p> <p>System power consumption (LED module &amp; driver) depends on components used</p>