

## OUTLED 2



Wall mounted direct / indirect IP54 LED luminaire.

|                                      |                               |
|--------------------------------------|-------------------------------|
| <b>Mounting:</b>                     | Directly on the wall          |
| <b>Body material:</b>                | Aluminium                     |
| <b>Colour:</b>                       | Standard White RAL 9016       |
| <b>LED module:</b>                   | LED module included           |
| <b>Colour temperature:</b>           | 3000K                         |
| <b>Colour Rendering Index (CRI):</b> | >80 in standard               |
| <b>Driver:</b>                       | Electronic driver in standard |
| <b>Emergency unit:</b>               | N/A                           |
| <b>Movement sensor:</b>              | N/A                           |
| <b>Daylight control sensor:</b>      | N/A                           |
| <b>Operating temperature range:</b>  | - 20°C ... +40°C              |
| <b>IP Class:</b>                     | IP54                          |
| <b>Power:</b>                        | 220-240V 50/60Hz              |
| <b>Lighting direction:</b>           | Direct / indirect             |
| <b>Reflector type:</b>               | Integrated lens               |
| <b>Light distribution:</b>           | Symmetric                     |
| <b>Diffusor:</b>                     | Clear glass                   |
| <b>General data:</b>                 | 3 Years standard warranty     |

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



| Index no.    | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI     | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|--------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 4596.400/830 | 400               | 5         | 3000             | Ra > 80 | 30.000       | 3                | 4              | 0,50        |

